

CLAIM AMENDMENTS**Claims pending:**

- At time of the Office Action: Claims 1-43.
- After this Response: Claims 1-25, 27-31, 34-35, and 37-43.

Canceled claims: 26, 32-33, and 36 without prejudice.

Amended claims: 1, 2, 9, 11-13, 16, 20, 28, 35, 37 and 40-41.

New Claims: None.

The listing of claims below will replace prior versions of claims in the application:

1. (Currently Amended) A computer-implemented method comprising:
receiving a plurality of events;
applying the plurality of events to a correlation function, wherein the correlation function is implemented as a state machine and is configured to correlate the plurality of events; ~~and~~
identifying an event to which an update consumer has subscribed, wherein the update consumer is associated with the state machine;
applying the update consumer to the state machine in response to the identified event; and
generating a specific event if the correlation function is satisfied by the plurality of events.

2. (Currently Amended) A method as recited in claim 1 wherein the ~~correlation function~~ update consumer is a class object.

3. (Original) A method as recited in claim 1 further including:
receiving a data element; and
applying the data element and at least one of the plurality of events to the correlation function.

4. (Original) A method as recited in claim 1 further including:
receiving a plurality of data elements; and
applying the plurality of data elements and the plurality of events to the correlation function.

5. (Original) A method as recited in claim 1 further including
communicating the specific event to at least one event consumer that subscribed to the specific event.

6. (Original) A method as recited in claim 1 further including continuing to receive additional events and apply the additional events to the correlation function if the correlation function is not satisfied by the plurality of events.

7. (Original) A method as recited in claim 1 further including resetting the correlation function after generating a specific event.

8. (Original) A method as recited in claim 1 further including:
creating an instance of a particular state machine; and
defining transitions for the particular state machine by subscribing to at
least one event.

9. (Currently Amended) A method as recited in claim 8 further including
deleting the instance of the particular state machine if the instance of the particular
state machine reaches a final state. applying an update consumer to the particular
state machine to update the state of the particular state machine.

10. (Original) One or more computer-readable memories containing a
computer program that is executable by a processor to perform the method recited
in claim 1.

11. (Currently Amended) A computer-implemented method comprising:
receiving a plurality of events;
receiving a plurality of data elements;
identifying a plurality of correlation functions configured to correlate the
plurality of events and the plurality of data elements, wherein each correlation
function is implemented with an associated state machine, and wherein each state
machine has an associated update consumer that updates the state of the associated
state machine;

applying the plurality of events and the plurality of data elements to the
plurality of correlation functions; and

generating a specific event if at least one of the plurality of correlation functions is satisfied.

12. (Currently Amended) A method as recited in claim 11 further comprising deleting a particular state machine when the particular state machine reaches a final state. ~~wherein each of the plurality of correlation functions is implemented as a state machine.~~

13. (Currently Amended) A method as recited in claim 11 wherein each of ~~the plurality of correlation functions~~ update consumer ~~is an instance of a class object.~~

14. (Original) A method as recited in claim 11 further including communicating the specific event to at least one event consumer that subscribed to receive the specific event.

15. (Original) A method as recited in claim 11 further including:
receiving additional events;
receiving additional data elements; and
applying the plurality of events, the additional events, the plurality of data elements and the additional data elements to the plurality of correlation functions.

16. (Currently Amended) A method as recited in claim ~~[[0]]~~ 11 further including:

receiving additional events;

receiving additional data elements;

receiving additional correlation functions; and

applying the plurality of events, the additional events, the plurality of data elements and the additional data elements to the plurality of correlation functions and the additional correlation functions.

17. (Original) A method as recited in claim 16 further including generating the specific event if at least one of the plurality of correlation functions or at least one of the additional correlation functions is satisfied.

18. (Original) A method as recited in claim 11 wherein the specific event generated is dependent on which correlation function is satisfied.

19. (Original) One or more computer-readable memories containing a computer program that is executable by a processor to perform the method recited in claim 11.

20. (Currently Amended) A computer-implemented method comprising:
identifying a schema for creating state machines, the state machines to
correlate at least two events;
creating an instance of a particular state machine;
defining transitions for the particular state machine by subscribing to at
least one event; and
applying an update consumer to the particular state machine to update the
state of the particular state machine, wherein the update consumer is a class object.

21. (Original) A method as recited in claim 20 further including deleting
the particular state machine if the particular state machine reaches a final state.

22. (Original) A method as recited in claim 20 wherein the particular state
machine includes a timer, the method further including deleting the particular state
machine if the timer expires.

23. (Original) A method as recited in claim 20 wherein the particular state
machine correlates at least one event and at least one data element.

24. (Original) A method as recited in claim 20 wherein the particular state
machine correlates a plurality of events and a plurality of data elements.

25. (Original) A method as recited in claim 20 further including determining a current state of the particular state machine.

26. (Canceled).

27. (Original) One or more computer-readable memories containing a computer program that is executable by a processor to perform the method recited in claim 20.

28. (Currently Amended) An apparatus comprising:

a plurality of event consumers; and

an event correlator coupled to the plurality of event consumers, the event correlator to receive events from at least one event source and to receive data elements from at least one data source, the event correlator further to receive at least one correlation function configured to correlate events and data elements and to apply the received events and the received data elements to the correlation function, wherein the correlation function is implemented by a state machine having an associated update consumer that updates the state of the state machine, and wherein the event correlator generates a specific event if the received events and the received data satisfy the correlation function.

29. (Original) An apparatus as recited in claim 28 wherein the event correlator communicates the specific event to the plurality of event consumers.

30. (Original) An apparatus as recited in claim 28 wherein the event correlator communicates the specific event to event consumers that have requested to receive the specific event.

31. (Original) An apparatus as recited in claim 28 wherein the event correlator communicates the specific event to a plurality of filters, wherein each of the plurality of filters is associated with one of the plurality of event consumers.

32-33. (Canceled).

34. (Original) An apparatus as recited in claim 28 wherein the event correlator continues to receive additional events and additional data elements and apply the additional events and the additional data elements to the correlation function.

35. (Currently Amended) One or more computer-readable media having stored thereon a computer program that, when executed by one or more processors, causes the one or more processors to:

receive a plurality of events;

identify a plurality of correlation functions configured to correlate the plurality of events, wherein each of the plurality of correlation functions is implemented as a state machine having an associated update consumer;

apply the plurality of events to the plurality of correlation functions to determine whether any of the plurality of correlation functions are satisfied by the

plurality of events, wherein the plurality of events are applied by causing update consumers associated with each event to update the state of the associated state machine; and

generate a specific event if one of the plurality of correlation functions is satisfied by the plurality of events.

36. (Canceled).

37. (Currently Amended) One or more computer-readable media as recited in claim 35 wherein ~~each of the plurality of correlation functions is implemented as a state machine, and wherein the state machine is a class object.~~

38. (Original) One or more computer-readable media as recited in claim 37 further causing the one or more processors to identify a current state of the state machine.

39. (Original) One or more computer-readable media as recited in claim 35 further causing the one or more processors to:

create a new instance of a state machine to implement a particular correlation function; and

define transitions for the new instance of the state machine by subscribing to at least one event.

40. (Currently Amended) A computer-implemented method comprising:

- receiving events from event providers;
- creating a first state machine;
- creating a second state machine;
- associating a first event type with the first state machine, wherein the first state machine has an associated first update consumer to update the state of the first state machine;
- associating a second event type with the second state machine, wherein the second state machine has an associated second update consumer to update the state of the second state machine;
- in response to receiving an event having a first event type, applying the first update consumer to the first state machine;
- in response to receiving an event having a second event type, applying the second update consumer to the second state machine; and
- ~~correlating the events using a function; and~~
- if the events are correlated[[,]] :
 - generating an additional event; and
 - sending the additional event to an event consumer.

41. (Currently Amended) The method as recited in claim 40, further comprising deleting the first state machine if the first state machine reaches a final state. [[:]]

- ~~receiving data from the event providers;~~
- ~~correlating the events and the data with the function; and~~

~~if at least one event and the data are correlated, generating the additional event.~~

42. (Previously Presented) The method as recited in claim 40, wherein the additional event is sent to the event consumer through a filter associated with the event consumer.

43. (Previously Presented) The method as recited in claim 40, wherein the event consumer includes at least one of an event logging consumer, an event forwarding consumer, a mail consumer, and a scripting consumer.